



Hi-Temp Red EP2 Grease

STARFIRE HI-TEMP RED EP2 GREASE is recommended for most automotive and industrial applications, including trucks, automobiles, construction equipment and heavy-duty industrial service. It is commonly recommended for wheel bearings, U-joints, chassis, and fifth wheels, as well as heavy duty industrial ball, roller and sleeve bearing designs. Hi-Temp Red EP2 Grease is licensed with NLGI to meet NLGI GC/LB specifications for automotive wheel bearings and chassis lubrication.

BENEFITS

- High-Temperature capability
- Excellent thermal and mechanical stability
- Oxidation and rust resistance
- Excellent water resistance
- Good low-temperature pumpability
- Extreme-pressure additive
- Compatible with lithium or lithium complex greases
- Excellent adhesion properties, tacky consistency

Typical Properties

NLGI Grade	2
Thickener	Lithium Complex
NLGI Classification	GC/LB
Worked Penetration	265-295
Dropping Point °C (°F), MIN	260 (550)
Four Ball Weld Point, KGF	400
Rust Protection	Pass 1,1,1
Water Washout @ 80°C, %	<5.0
Timken OK Load, lbs	50
Base Oil Viscosity @ 40°C cSt	220
Approximate Temp Range, °C (°F)	-18 to 129 (0 to 265)

